

Standard Features

MODEL	GB-C350
Standby Power(60Hz)	308KW/385KVA
Prime Power(60Hz)	280KW/350KVA
Engine	Cummins NTA855-G1B
Alternator	STAMFORD HCI444D

- **Engine(CCEC Cummins NTA855-G1B)**
- Radiator 40°C max, fans are driven by belt, with safety guard
- 24V charge alternator
- **Alternator(STAMFORD HCI444D),**
- single bearing alternator, Protection Class IP22, insulation class H/H
- Dry Type air filter, fuel filter, oil filter, pre-filter, absorber
- Main line circuit breaker
- Standard control panel
- Two 12V batteries, rack and cable
- Ripple flex exhaust pipe, Exhaust siphon, flange, muffler
- Operation manual



Generator Set Ratings						
Voltage	Frequency	Phase	P.F (COS ϕ)	Standby Amps	Standby Ratings (KW/KVA)	Prime Ratings (KW/KVA)
440/230	60	3	0.8	505	308/385	280/350
416/220	60	3	0.8	535	308/385	280/350
220/127	60	3	0.8	1110	308/385	280/350

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820-97 (equiv ISO8528); A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation. Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency

Dimension Of Generator Set	
Dimension(L*W*H)/CM For Open Type	302×110×190CM
Net Weight/KG For Open Type	3300KG
Dimension(L*W*H)/CM For Sound Proof Type	423×146×215 CM
Net Weight/KG For Sound Proof Type	4300 KG
Dimension (L*W*H)/MM For Trailer Type	
Net Weight/KG For Trailer Type	

Specification Of Engine		
Engine	Engine Model	NTA855-G1B
	Manufacturer	CCEC Cummins
	Prime Power	315KW/428HP
	Standby Power	347KW/472HP
	Engine Configuration	6Cylinder In Line, 4Stroke
	Gas Feeding Model	Turbocharged
	Bore×Stroke	140×152 (MM)
	Displacement	14L
	Rated Speed	1800RPM
	Speed Governor	Electronic
	Starter Model	24V DC Start
	Fuel Consumption Standby Power (100% load)	70L/H
	Oil Consumption	≤4 g/kw.h
	Cooling System	Water Cool
	Compression Ratio	14.5:1
	Max Back Pressure	10KPA
	Max Intake Restriction	6.25KPA
	Exhaust Temperature	543℃

Specification Of Alternator


Alternator	Alternator Model	HCI444D
	Manufacturer	STAMFORD company
	Prime Output	280KW/350KVA
	Standby Output	308KW/385KVA
	Excitation Model	Brushless, Self-Exciting
	Cooling Method	Air Cooling
	Connection Type	3 Phase and 12 Wires "Star" Connection
	Power Factor	0.8
	Protection Class	IP22
	Insulation Class	H
	Altitude	≤1000m
	Voltage Regulation, Steady State	≤ ± 1%
	Telephone Influence Factor	< 50
	Sudden Voltage Warp (100% Sudden Reduce)	≤ ± 1%
	Sudden Voltage Warp (Sudden Increase)	≤ ± 25%
	Voltage Stable Time (100% Sudden Reduce)	≤ 6S
	Voltage Stable Time (Sudden Increase)	≤ 6S
	Frequency Reduce	0-5% adjustable
	Frequency Regulation, Stead State	≤ 1.5%
	Frequency Waving	≤ 0.8%
	Sudden Frequency Warp (100% Sudden Reduce)	≤ +12%
Sudden Frequency Warp (100% Sudden Increase)	≤ -10%	
Frequency Recovery Time (100% Sudden Reduce)	≤ 5S	
Frequency Recovery Time (Sudden Increase)	≤ 5S	
Compliance Stands	GB755,BS5000,VDE0530,NEMAMG1-22,IED34-1,CSA22.2 and AS1359	

Control Panel System



DEEPSEA501K CONTROL MODEL/ MANUAL OR USE
 With Four Protection
 1.High water Temperature Shutdown
 2. Low Oil Pressure Shutdown
 3. Over Speed Shutdown 4. Over Crank Shutdown
 5. Protection as Emergent Stop
Parameters of Operation:
 1. Emergency Stop Button 2.Voltmeter and Selector Switch
 3. Ammeter and Selector Switch 4. Frequency Meter

Control Panel System



DEEPSEA6020 CONTROL MODEL/ MANUAL OR ATS USE
 With Four Protection
 1.High water Temperature Shutdown
 2. Low Oil Pressure Shutdown
 3. Over Speed Shutdown
 4. Over Crank Shutdown
 5. Protection as Emergent Stop
Parameters of Operation:
 Digital type, all function showed by LED

Control Panel System



DEEPSEA7320 CONTROL MODEL/ MANUAL OR ATS USE
 With Four Protection
 1.High water Temperature Shutdown
 2. Low Oil Pressure Shutdown
 3. Over Speed Shutdown
 4. Over Crank Shutdown
 5. Protection as Emergent Stop
 6. With Remote Teleport Communication RS 485
Parameters of Operation: