

Standard Features	
MODEL	GB-300
Standby Power(50Hz)	330KW/413KVA
Prime Power(50Hz)	300KW/375KVA
Engine	GB POWER GB-135TAD28
Alternator	GB POWER GB-HCI444D

- **Engine(GB POWER GB-135TAD28)**
- Radiator 40°C max, fans are driven by belt, with safety guard
- 24V charge alternator
- **Alternator(GB POWER GB-HCI444D),**
- single bearing alternator, Protection Class IP23, insulation class H/H
- Dry Type air filter, fuel filter, oil filter, pre-filter, absorber
- Main line circuit breaker
- Standard control panel
- Two 12V batteries, rack and cable
- Ripple flex exhaust pipe, Exhaust siphon, flange, muffler
- Operation manual



Generator Set Ratings						
Voltage	Frequency	Phase	P.F (COS ϕ)	Standby Amps	Standby Ratings (KW/KVA)	Prime Ratings (KW/KVA)
400/230	50	3	0.8	596	330/413	300/375
380/220	50	3	0.8	627	330/413	300/375

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820-97 (equiv ISO8528); A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation. Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency

III

Dimension Of Generator Set	
Dimension(L*W*H)/CM For Open Type	370×148×220 CM
Net Weight/KG For Open Type	4500 KG
Dimension(L*W*H)/CM For Sound Proof Type	530×165×225 CM
Net Weight/KG For Sound Proof Type	5100 KG
Dimension (L*W*H)/MM For Trailer Type	
Net Weight/KG For Trailer Type	

Specification Of Engine		
Engine	Engine Model	GB-135TAD28
	Manufacturer	GB POWER
	Prime Power	280KW/380HP
	Standby Power	308KW/419HP
	Engine Configuration	12Cylinder V Shape, 4Stroke,Direct Injection
	Gas Feeding Model	Turbo Charged
	Bore×Stroke	135*150 (MM)
	Displacement	25.8L
	Idle speed	700RPM
	Rated Speed	1500RPM
	Speed Governor	Mechanical/Electric Speed Control System
	Starter Model	24V DC Start
	Fuel Consumption Prime Power (100% load)	67.4L/KW.H
	Compression Ratio	16: 1
	Oil Consumption	G/KW.H
	Cooling System	Water Cool
	Noise	≅ 117dB
Smoke	≅ 2FSN	
Stable state rate	5%	

Specification Of Alternator		
Alternator	Alternator Model	HCI444D
	Manufacturer	GB POWER CO.,LTD.
	Prime Output	240KW/300KVA
	Standby Output	264KW/330KVA
	Excitation Model	Brushless, Self-Exciting
	Cooling Method	Air Cooling
	Connection Type	3 Phase and 12 Wires "Star" Connection
	Power Factor	0.8
	Protection Class	IP22
	Insulation Class	H
	Altitude	≤1000m
	Voltage Regulation, Steady State	≤ ± 1%
	Telephone Influence Factor	< 50
	Sudden Voltage Warp (100% Sudden Reduce)	≤ ± 1%
	Sudden Voltage Warp (Sudden Increase)	≤ ± 25%
	Voltage Stable Time (100% Sudden Reduce)	≤ 6S
	Voltage Stable Time (Sudden Increase)	≤ 6S
	Frequency Reduce	0-5% adjustable
	Frequency Regulation, Stead State	≤ 1.5%
	Frequency Waving	≤ 0.8%
	Sudden Frequency Warp (100% Sudden Reduce)	≤ +12%
	Sudden Frequency Warp (100% Sudden Increase)	≤ -10%
	Frequency Recovery Time (100% Sudden Reduce)	≤ 5S
Frequency Recovery Time (Sudden Increase)	≤ 5S	
Compliance GB755,BS5000,VDE0530,NEMAMG1-22,IED34-1,CSA22.2 and AS1359 Stands		

Control Panel System



DEEPSEA 501K CONTROL MODEL/ MANUAL USE

With Four Protection

- 1.High water Temperature Shutdown
2. Low Oil Pressure Shutdown
3. Over Speed Shutdown
4. Over Crank Shutdown
5. Protection as Emergent Stop

Parameters of Operation:

1. Emergency Stop Button
- 2.Voltmeter and Selector Switch
3. Ammeter and Selector Switch
4. Frequency Meter
5. Hour Running Meter
- 6.Alart Buzzer



DEEPSEA 6020 CONTROL MODEL/ MANUAL OR ATS USE

With Four Protection

- 1.High water Temperature Shutdown
2. Low Oil Pressure Shutdown
3. Over Speed Shutdown
4. Over Crank Shutdown
5. Protection as Emergent Stop

Parameters of Operation:

Digital type, all function showed by LED



DEEPSEA 7320 CONTROL MODEL/ MANUAL OR ATS USE

With Four Protection

- 1.High water Temperature Shutdown
2. Low Oil Pressure Shutdown
3. Over Speed Shutdown
4. Over Crank Shutdown
5. Protection as Emergent Stop

Parameters of Operation:

Digital type, all function showed by LED