

Standard Features

MODEL	GB-P35
Standby Power(60Hz)	30KW/38KVA
Prime Power(60Hz)	28KW/35KVA
Engine	PERKINS 1103A-33G
Alternator	STAMFORD PI144G

- **Engine(PERKINS.UK 1103A-33G)**
- Radiator 40°C max, fans are driven by belt, with safety guard
- 24V charge alternator
- **Alternator(STAMFORD PI144G),**
- single bearing alternator, Protection Class IP23, insulation class H/H
- Dry Type air filter, fuel filter, oil filter, pre-filter, absorber
- Main line circuit breaker
- Standard control panel
- Two 12V batteries, rack and cable
- Ripple flex exhaust pipe, Exhaust siphon, flange, muffler
- Operation manual



Generator Set Ratings						
Voltage	Frequency	Phase	P.F (COS ϕ)	Standby Amps	Standby Ratings (KW/KVA)	Prime Ratings (KW/KVA)
220/127	60	3	0.8	98	30/38	28/35
208/120	60	3	0.8	104	30/38	28/35

Prime Power(PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820-97 (equiv ISO8528); A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation. Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency

Dimension Of Generator Set	
Dimension(L*W*H)/CM For Open Type	165×75×125 CM
Net Weight/KG For Open Type	700KG
Dimension(L*W*H)/CM For Sound Proof Type	250×100×157 CM
Net Weight/KG For Sound Proof Type	1250KG
Dimension (L*W*H)/MM For Trailer Type	
Net Weight/KG For Trailer Type	

Specification Of Engine		
Engine	Engine Model	1103A-33G
	Manufacturer	PERKINS UK
	Emissions statement	EU2007(EU97/68/EC Stage II) EPA Tier 4Final(EPA 40 CFR Part 1039 Tier 4)
	Prime Power	32.2KW/43.1HP
	Standby Power	35.4KW/47.4HP
	Engine Configuration	3Cylinder In Line, 4Stroke,Direct Injection
	Gas Feeding Model	Natural Aspiration
	Bore×Stroke	105×127 (MM)
	Displacement	3.3L
	Rated Speed	1800RPM
	Speed Governor	Electrical
	Starter Model	12V DC Start
	Fuel Consumption Prime Power (100% load)	8.6L/H
	Totally lubrication system Capacity	7.9L
	Coolant capacity	10.2L
	Cooling System	Water Cool
Compression Ratio	19.25:1	


Specification Of Alternator		
Alternator	Alternator Model	PI144G
	Manufacturer	STAMFORD company
	Prime Output	28KW/35KVA
	Standby Output	30.8KW/38.5KVA
	Excitation Model	Brushless, Self-Exciting
	Cooling Method	Air Cooling
	Connection Type	3 Phase and 12 Wires "Star" Connection
	Power Factor	0.8
	Protection Class	IP22
	Insulation Class	H
	Altitude	≤ 1000m
	Voltage Regulation, Steady State	≤ ± 1%
	Telephone Influence Factor	< 50
	Sudden Voltage Warp (100% Sudden Reduce)	≤ ± 1%
	Sudden Voltage Warp (Sudden Increase)	≤ ± 25%
	Voltage Stable Time (100% Sudden Reduce)	≤ 6S
	Voltage Stable Time (Sudden Increase)	≤ 6S
	Frequency Reduce	0-5% adjustable
	Frequency Regulation, Stead State	≤ 1.5%
	Frequency Waving	≤ 0.8%
Sudden Frequency Warp (100% Sudden Reduce)	≤ +12%	
Sudden Frequency Warp (100% Sudden Increase)	≤ -10%	
Frequency Recovery Time (100% Sudden Reduce)	≤ 5S	
Frequency Recovery Time (Sudden Increase)	≤ 5S	
Compliance Standards	GB755,BS5000,VDE0530,NEMAMG1-22,IED34-1,CSA22.2 and AS1359	

Control Panel System



DEEPSEA501K CONTROL MODEL/ MANUA USE
 With Four Protection
 1.High water Temperature Shutdown
 2. Low Oil Pressure Shutdown
 3. Over Speed Shutdown 4. Over Crank Shutdown
 5. Protection as Emergent Stop
Parameters of Operation:
 1. Emergency Stop Button 2.Voltmeter and Selector Switch
 3. Ammeter and Selector Switch 4. Frequency Meter
 5. Hour Running Meter6.Alart Buzzer

Control Panel System



DEEPSEA6020 CONTROL MODEL/ MANUAL OR ATS USE
 With Four Protection
 1.High water Temperature Shutdown
 2. Low Oil Pressure Shutdown
 3. Over Speed Shutdown
 4. Over Crank Shutdown
 5. Protection as Emergent Stop
Parameters of Operation:
 Digital type, all function showed by LED

Control Panel System



DEEPSEA CONTROL MODEL/ MANUAL OR ATS USE
 With Four Protection
 1.High water Temperature Shutdown
 2. Low Oil Pressure Shutdown
 3. Over Speed Shutdown
 4. Over Crank Shutdown
 5. Protection as Emergent Stop
 6. With Remote Teleport Communication RS 485
Parameters of Operation:
 Digital type, all function showed by LED